

**GENERAL INFORMATION:**

- A special effect decorative paint based on Acrylic emulsion resin.
- Suitable both for unique home styling and public areas such as hotels, restaurants, offices and more.
- Decorative effect for both interior and exterior walls.
- **Safari Natural (SW):** semi-opaque look in desert shades.
- **Safari Perlato (SP):** semi-opaque pearl look.
- **Safari White Pearl (WSP):** opaque pearl look (more sand)
- **Safari Perlato Glitter (SPG):** Sparkling glitter.

**FEATURES:**

- ✓ Odorless.
- ✓ Unique decorative with Sand Art texture.
- ✓ Good color retention.
- ✓ Ready to use – not dilute

**CERTIFICATION:**

- ✓ Quality Management ISO9001.
- ✓ Environment Management ISO14001.
- ✓ Health & Safety management OEHSA ISO18001.

**TECHNICAL DATA:**

Binder type:	Acrylic emulsion	Color shade:	Tambour color collection
Solid content by volume:	40.50%	Humidity limit:	less than 85%
Solid content by weight:	60.36%	Application temperature:	Min: 10°C Max: 40°C
PH value:	8.5-9.5	Drying time:	Touching(*): 1 hour Re-coat: 3 hours Completed: 72 hours
Thinner:	NA	Drying method:	Coealescence & evaporation
Viscosity:	12000-15000cps	Calculated coverage (**):	4-6 m <sup>2</sup> /l ( in 1 coat)
Density:	1.50 g/cm <sup>3</sup>	Gloss:	NA
Packsize	3l		
Storage:	below 30°C		
Shelf-life:	2 years		

Free of lead and Chromates. Product is not self-igniting and not present an explosion hazard.

\* At 25°C and 65% humidity.

\*\* The actual coverage rate can vary, depending on the surface, the application mode, the painter's skill and weather conditions at the site. Assume approximately 75% of the calculated coverage ability.

**SURFACE PREPARATION:**

Remove any old, loose and peeling paint. Clean the wall from dirt and dust. Apply one coat of Tambour recommended paint tinted in a similar shade to the chosen Safari shade. If the surface is painted with lime paint, apply one coat of Tambour recommended primer before applying Tambour recommended paint. Make sure that the surface was prepared in accordance with IS 1920 part 1 and 2.

**APPLICATION GUIDE:**

Stir the paint well before application and while painting.

**To obtain the wild dune look on a smooth background:** It is recommended to apply first on a small area and choose the preferred texture. Dip a brush (3" – 4" wide) in the paint container. Apply a small quantity of the paint on the wall in wide crisscross movements. After covering a defined area, continue to 'play' in a free hand with the paint on

the wall, applying it repeatedly until islands of dune-like texture are created next to smooth areas (hills and ravines). It is recommended to apply over a diagonal section of about 0.5 sqm. at a time to ensure complete coverage. It is recommended to step away from the wall occasionally during the application to view the entire wall. If you wish to obtain a higher paint density, continue to load the brush with paint and apply. Watch out for areas with excess amount of paint. If it tends to run, continue to spread the paint. Use a dry brush to brush lightly in one direction to obscure brush marks.

**Notice:** Do not accelerate drying with a ventilator or a heat blower, to prevent splintering and cracks. The final shade and look is affected by the direct lighting on the wall and by the reflection of the light on the wall.

## SAFETY INFORMATION:

**Cleanup and Storage:** Clean work tools with soap and water immediately after use. Close the container tightly to prevent air penetration. Store in a roofed and ventilated place, below 30°C.

**Cautions:** The paint is inedible, the paint is not defined as a dangerous substance and does not contain materials requiring special markings or warnings. Keep out of reach of children. Use in a well ventilated area only. Specific information regarding the product is available in the safety manual (MSDS).

**General Notes:** Do not apply when the wall is wet or when it is expected to rain before or after the application and/or the wall temperature is below 10°C and the relative humidity is above 85%. For cracked walls use the Tambourflex Paint System. Do not mix this product with products not recommended by us. Achieving desired results is dependent on the proper application of the product while following all instructions. Before applying the product, the user must make sure that the product is indeed designed for the intended usage and that the surfaces to be painted are properly prepared and suitable for the product's application. Data presented here is based on our best knowledge and experience. We reserve the right to update and/or change it at our discretion.

*Manufactured by Tambour, a company with a quality assurance system that meeting the requirements of Israeli Standards ISO 9001, ISO 18001, ISO 14001 and accredited by the Israel Institute of Standards in compliance with them.*